

## Claims

1. A network node for use in a WDM communications network, the network node comprising:

- a first network interface unit arranged, in use, to demultiplex an incoming WDM optical signal and to convert the incoming WDM optical signal into a plurality of electrical channel signals,

- a regeneration unit for regenerating the electrical channel signals utilising at least 2R regeneration,

- a second network interface unit arranged, in use, to convert and multiplex at least one of the electrical channel signals into an outgoing WDM optical signal, and

- a secondary interface unit arranged, in use, to convert at least one of the electrical channel signals into an optical signal and to drop the optical signal at the network node.

2. A network node as claimed in claim 1, wherein the secondary interface unit is further arranged, in use, to receive at least one single wavelength optical signal and to convert it into a corresponding electrical signal, and the second network interface unit is further arranged to convert and multiplex the corresponding electrical signal into the outgoing WDM optical signal.

3. A network node as claimed in claim 2, wherein the secondary interface unit is arranged, in use, to regenerate the corresponding electrical signal utilising at least 2R regeneration.

4. A network node as claimed in claim 1, wherein the network node further comprises an electrical switching unit arranged, in use, to facilitate that any electrical channel signal can selectively be converted and dropped at the network node via the secondary interface unit or converted and multiplexed into the outgoing WDM signal via the second network interface unit.

5. A network node as claimed in claim 1, wherein the first network interface unit comprises at least one trunk interface card for converting respective channels of the incoming WDM optical signal into the electrical channel signals.

202011061201

17. A network node for use in a WDM communications network, the network node comprising:

- a first network interface unit arranged, in use, to demultiplex an incoming WDM optical signal and to convert the incoming WDM optical signal into a plurality of electrical channel signals,

- a regeneration unit for regenerating the electrical channel signals utilising at least 2R regeneration,

- a second network interface unit arranged, in use, to convert and multiplex at least one of the electrical channel signals into an outgoing WDM optical signal, and

- a secondary interface unit arranged, in use, to receive at least one single wavelength optical signal and to convert it into a corresponding electrical signal,

and the second network interface unit is further arranged to convert and multiplex the corresponding electrical signal into the outgoing WDM optical signal.

18. A WDM network incorporating at least one network node as defined in claims 1 or 17.

19. A method of transmitting communication data in a WDM communications network, the method comprising the steps of, at a network node of the WDM communications network:

- demultiplexing an incoming WDM optical signal
- converting the incoming WDM optical signal into a plurality of electrical channel signals,
- regenerating the electrical channel signals utilising at least 2R regeneration,
- converting and multiplexing at least one of the electrical channel signals into an outgoing WDM optical signal,
- converting at least one of the electrical channel signals into an optical signal;
- and dropping the optical signal at the network node.

20. A method of transmitting communication data in a WDM communications network, the method comprising the steps of, at a network node of the WDM communications network:

- demultiplexing an incoming WDM optical signal

- converting the incoming WDM optical signal into a plurality of electrical channel signals,
- regenerating the electrical channel signals utilising at least 2R regeneration,
- converting and multiplexing at least one of the electrical channel signals into an outgoing WDM optical signal,
- receiving at least one single wavelength optical signal,
- converting it into a corresponding electrical signal,
- converting and multiplexing the corresponding electrical signal into the outgoing WDM optical signal.

090074-061001  
T09T90-4T09090